

Basement Waterproofing

Basement waterproofing is a critical component of below-ground construction, forming the primary defence against water ingress, dampness, and long-term structural degradation. Ensuring a dry, resilient, and durable environment is essential for the functional use of basement spaces, and to preserve the integrity, value, and lifespan of the building.

This Loss Prevention Standard provides risk management guidance on basement waterproofing.

Basement Waterproofing

Introduction

Basement waterproofing is a fundamental aspect of below-ground construction, providing essential protection against water ingress, dampness, and long-term structural deterioration. As basements continue to be incorporated into modern developments, and the effects of climate change and rising water levels become more prevalent, the performance expectations placed upon waterproofing systems have grown significantly.



Achieving a dry, durable, and resilient basement environment is therefore critical not only for the functionality of the space, but also for maintaining the value, safety, and longevity of the overall structure.

Inadequate or poorly executed waterproofing can lead to substantial and costly consequences. These risks underscore the importance of early strategic planning, robust detailing, the correct specification of systems, and the involvement of suitably qualified specialists throughout the design and construction process.

Successful waterproofing requires a holistic approach that considers a wide range of influencing factors, including the geology, hydrogeology, and topography of the site; groundwater behaviour; soil contaminants; structural detailing; and the intended end use of the basement space.

Understanding the Risks

- **Water Ingress Through Membranes or Joints.** Water penetrates a basement structure at its most vulnerable points, such as membrane laps, joints, penetrations, and transitions between different materials. Even small discontinuities or poorly sealed junctions can allow moisture to track behind the system, eventually causing leaks internally.
- **Hydrostatic Pressure Causing Structural Stress.** Below ground structures are frequently subjected to significant hydrostatic pressure, particularly where the groundwater table is high or fluctuates seasonally. This pressure exerts continuous force on walls and slabs, increasing the likelihood of cracking, joint displacement, or even structural movement if the design is inadequate. Waterproofing systems that are not designed to withstand these loads may fail prematurely under stress.
- **Condensation and Vapour Related Issues.** Even where liquid water is successfully excluded, internal moisture problems can occur due to vapour diffusion, temperature differences, or inadequate ventilation. Condensation often forms on cold surfaces, encouraging mould growth, material decay, and deterioration of finishes. Vapour ingress can also make spaces feel damp or humid, impacting the usability of the basement environment—particularly in higher grade areas.

- **Incorrect Waterproofing System Selection.** Choosing a system inconsistent with the basement's intended use, ground conditions, or performance requirements can result in underperformance or failure. For example, relying solely on an externally installed system, or specifying reactive additives within the concrete where no dampness can be tolerated, can introduce unacceptable risk. Proper assessment of site conditions and an understanding of system limitations are essential for correct specification.
- **Poor Workmanship at Details or Joints.** Waterproofing performance depends heavily on installation quality. Many failures occur not in the main field areas but at details—corners, edges, joints, service penetrations, pile heads, and interfaces with other construction elements. Poor preparation, insufficient supervision, and improper installation techniques can create weak points where leaks later emerge. Repairing defects after completion is often invasive and expensive.
- **Difficulty of Remediation Once Complete.** Once water finds a path of least resistance, it often spreads unseen behind membranes, making detection and repair difficult. When a basement structure is backfilled or fully constructed, accessing failed waterproofing systems becomes extremely challenging. External membranes may be buried several metres below ground, while internal systems may sit behind finishes, services, or structural elements. Remedial works therefore tend to be disruptive, costly, and sometimes only partially effective. Preventing failure through appropriate design and installation is far more efficient than attempting repairs later.
- **Lack of Specialist Design Involvement.** Waterproofing is a specialist discipline, and errors often arise when general designers or contractors attempt to manage it without adequate expertise. The latest version of **BS 8102 'Code of Practice for Protection of Below Ground Structures Against Water from the Ground'** emphasises the need for a qualified waterproofing specialist to guide system selection, risk assessment, detailing, sequencing, and integration with the structural design. Without specialist oversight, critical risks may be overlooked, leading to incompatible or insufficiently robust solutions.

Managing the Risks

Compliance

Basement waterproofing should always comply with BS 8102. This British Standard sets out the requirements and makes recommendations for waterproofing in new-build basements. The standard forms the basis of waterproofing analysis and design; defines waterproofing system types and performance grades; and provides advice on how the specified performance may be achieved.

Use Established and Certified Waterproofing Products

Selecting products that are independently tested, certified, and compliant with recognised industry standards significantly reduces the risk. This ensures that the materials used are appropriate for below-ground environments and provide predictable, reliable performance throughout the design life of the structure. Using untested or proprietary materials without certification can introduce unknown risks and complications.

Specialist Designers and Trained Installers

Waterproofing is a specialist discipline that requires a thorough understanding of material behaviour, structural interaction, sequencing, and detailing. Engaging experienced waterproofing designers (i.e., CSSW or WDS accreditation) ensures that the system is specified correctly and is co-ordinated with the structural and architectural design. Proper specialist involvement ensures that details such as joints, penetrations, and interfaces are designed and executed to a standard that prevents water ingress.

Supervision Throughout Installation

High quality supervision ensures that surfaces are prepared correctly, environmental conditions are suitable, overlaps and terminations are installed properly, and workmanship issues are addressed immediately. Competent supervision also ensures adherence to manufacturer guidelines and British Standards and records compliance throughout construction.

Compatibility With Existing Structures

Where new waterproofing works interface with existing structures—such as extensions, refurbishments, or retained basement walls—compatibility becomes essential. Differences in material behaviour, movement characteristics, or surface preparation requirements can create weaknesses where water may penetrate. Ensuring compatibility includes assessing the condition of the existing substrate, selecting systems that bond appropriately, and designing transitions that maintain continuity of protection.

Durability and Maintenance Requirements

Waterproofing systems must provide reliable performance throughout the intended design life of the structure. Durability considerations include resistance to hydrostatic pressure, mechanical damage, and long-term material degradation. Additionally, some systems, such as Cavity Drain Systems, require ongoing maintenance, e.g., pump servicing, drainage channel cleaning, and system inspections. Designing for durability ensures long term resilience, while designing for maintenance ensures that the system remains functional and compliant over time. Lack of maintenance planning can lead to avoidable failures later in the building's lifecycle.

Inspections

Thorough inspection (both during and after installation) is essential to verify that waterproofing systems have been applied correctly and without defects. Inspections may include visual checks, adhesion tests, flood testing (where appropriate), detailed photographic records, and manufacturer sign-off. Early detection of defects allows corrective action while the structure is still accessible. A well-documented inspection process provides traceability, supports quality assurance, and reduces the risk of latent defects going unnoticed until after the building is occupied.

Understanding the British Standard

Grades of Waterproofing

Waterproofing protection within basements is specified in accordance with BS 8102, with four distinct grades of waterproofing performance. Whilst BS 8102 does not provide guidance on basement usage, the following may be used as broad guidance for levels of waterproofing protection within specific basement environments:

- **Grade 1a.** Typically specified where the presence of minor water leaks may be tolerated.
- **Grade 1b.** Typically specified where some damp and moisture may be tolerated.
- **Grade 2.** Typically specified where no seepage is acceptable, and no damp from water ingress can be tolerated; however, some condensation may be acceptable.
- **Grade 3.** The most onerous environment. When specified it **MUST** incorporate ventilation, dehumidification or air conditioning to comply with the requirements of the standard.

Types of Waterproofing Defence

BS 8102 recognises three standard types of waterproofing protection systems:

- **Type A (Barrier) Protection.** These involve the application of a barrier system onto the face of the basement walls and slabs to obstruct water flow paths through the substructure, i.e., the basement structures are not themselves relied upon to prevent water ingress.

Barrier protection systems typically incorporate a waterproof membrane either in sheet form or liquid form to the outer or inner face of the structure. Internal membranes are inherently vulnerable to the effects of hydrostatic pressure as water permeates through the non-watertight structure behind them.

- **Type B (Structurally Integral) Protection.** This method of protection relies upon the basement structure, i.e., the substructure slabs and walls to provide inherent waterproofing protection. This means the structure is itself formed as a watertight construction that requires no additional protection. Water resistant concrete is generally achieved through either controlling crack width or using water-resisting concrete mixes.
- **Type C (Drained) Protection.** This form of protection relies upon an internal ventilated cavity to channel water and drain it away. Water entering the structure is received by planned cavities or voids and diverted into drainage channels from where it is safely removed by pumped systems. For a drained protection system to be effective the cavity should be constructed in both the walls and the floor of the substructure. Ventilation/drainage requirements of this form of protection should not be overlooked; as well as associated installation expense, they require maintenance through the structure's life.

Combined Waterproofing Systems

Combined systems of waterproofing are used in design situations where the basement waterproofing grade specified does not tolerate seepage. Where a combination is being considered, systems should have different performance characteristics to mitigate the risk of failure due to a common cause. Often other factors will dictate the use of a second or third type of protection, such as ground gases or aggressive agents found within the groundwater.

The end use of the building will influence the type of waterproofing selected. The waterproofing should be maintainable.

Recommendations for New-Build Basements

The key to a dry new-build basement is a structure capable of providing primary resistance to the expected water pressure. A well-designed/placed concrete structure, with correctly designed reinforcing steel, will require attention only at the construction joints to become a Type B waterproofed structure that will be suitable for Grade 1a environments. This also produces a good starting point ready for waterproofing to higher grades with other waterproofing types and products.

Recommendations for Existing Basements

Existing basements differ from new-build basements due to the difficulty in ascertaining the protection measures currently in place as well as potential complications. These include limited space for new systems; increased costs associated with remedial works and access for investigation. For this reason, Type C systems offer the most robust remedial options. Whilst internal tanking solutions are generally not considered appropriate for new build basements, they may be applied as part of remedial works programmes within existing basements where the outer face cannot be accessed.

Geology, Hydrogeology and Topography

BS8102 advises that designers need to be certain that examinations are conclusive and demonstrable before deciding on the risk associated with water pressure on the structure. Where comprehensive current and historical site investigations are not available, or the results are inconclusive, the design should ensure both the structure and the waterproofing are able to withstand a full head of hydrostatic water pressure.

Inclusion of a Waterproofing Specialist as Part of the Design Team

A significant factor in the recommendations of BS 8102 is the inclusion of a waterproofing specialist in the design team. This ensures that a capable and competent expert is able to influence the waterproofing design at concept stage so that an appropriate integrated waterproofing solution can be developed

The waterproofing specialist should be a certified Surveyor in Structural Waterproofing (CSSW) and/or a certified Waterproofing Design Specialist (WDS). The following should also be followed:

- All design decisions that may have an impact on the waterproofing design **MUST** be brought to the attention of the waterproofing specialist/designer.
- Final decisions and/or recommendations should be approved by the waterproofing specialist.
- The waterproofing specialist should produce a project-specific waterproofing risk assessment which takes account of:
 - ✓ The prevailing ground conditions,
 - ✓ The groundwater level locally,
 - ✓ The severity of the hazard,
 - ✓ The potential consequences of a significant failure of the waterproofing system,
 - ✓ The scale, scope and methodology of any associated programme of remedial works.

The waterproofing risk assessment will inform the development of the waterproofing design.

Key Actions

The points below must be considered when evaluating basement waterproofing proposals:

- A waterproofing specialist should be included within the project team. This should be an independent specialist without affiliation to any specific product or system supplier.
- The specification of a basement waterproofing grade should be appropriate to the intended usage of the basement.
- In basements where higher-grade performance is specified the default position should be for a combined system comprising at least two different types of waterproofing defence.
- Type B reactive waterproofing systems should generally be avoided for any higher-grade areas, however, may be used in combination with a Type C system to achieve all grades of waterproofing.
- Where Grade 3 waterproofing is specified the design **MUST** incorporate ventilation, dehumidification or air conditioning as necessary; appropriate to the intended use.
- Type C systems can have the lowest inherent risk of failure of the three forms of defence. However, it is not unusual to have a Type A system incorporated below basement slabs in place of a Type C system.

Specialist Partner Solutions

Aviva Risk Management Solutions can offer access to a wide range of risk management products and services at preferential rates via our network of Specialist Partners.

For more information please visit: [Aviva Risk Management Solutions – Specialist Partners](#)

Sources and Useful Links

- [BS8102: Protection of below ground structures against water ingress. Code of practice](#)

Note: Whilst UK standards and legislation are referenced in this document, other international standards and legislation should be referenced where applicable.

Additional Information

Relevant Aviva Loss Prevention Standards include:

- **Low Carbon Concrete - Introduction**
- **Delivering Successful Construction Projects**
- **Requirements for Re-use of Structural Steel in the United Kingdom**
- **Zero Falls Roofs - Considerations (RIBA Stages 0 to 6)**

To find out more, please visit [Aviva Risk Management Solutions](#) or speak to one of our advisors.

Email us at riskadvice@aviva.com or call 0345 366 6666.*

*The cost of calls to 03 prefixed numbers are charged at national call rates (charges may vary dependent on your network provider) and are usually included in inclusive minute plans from landlines and mobiles. For our joint protection telephone calls may be recorded and/or monitored.

Please Note

This document contains general information and guidance only and may be superseded and/or subject to amendment without further notice. Aviva has no liability to any third parties arising out of ARMS' communications whatsoever (including Loss Prevention Standards), and nor shall any third party rely on them. Other than liability which cannot be excluded by law, Aviva shall not be liable to any person for any indirect, special, consequential or other losses or damages of whatsoever kind arising out of access to, or use of, or reliance on anything contained in ARMS' communications. The document may not cover every risk, exposure or hazard that may arise, and Aviva recommend that you obtain specific advice relevant to the circumstances.

19th March 2026

Version 1.0

ARMSGI3992026

Aviva Insurance Limited, Registered in Scotland Number SC002116. Registered Office: Pitheavlis, Perth PH2 0NH.
Authorised by the Prudential Regulation Authority and regulated by the Financial Conduct Authority and the Prudential Regulation Authority.